

PREMIUM SERIES

8360

DC BATTERY BACKUP
CHAIN DRIVE
GARAGE DOOR OPENER



Secure And Reliable. This Garage Door Opener Is Quite A Catch.

- Get in your garage every time, even when the power is out. The Battery Backup System ensures your garage door opener, as well as the safety and security features, will continue to work.
- Energy-efficient operation consumes up to 75% less power in standby mode.
- Industrial-strength chain drive system provides steady performance and lifting power.
- Lifetime motor warranty.
- 1-year parts warranty.
- 1-year warranty on Battery Backup battery.



Simple Control From Anywhere

A first ever in garage door openers, the new LiftMaster® Premium Series model 8360 DC Battery Backup Chain Drive is built with MyQ™ technology, a patented two-way communication system. Smarter on the inside and designed to do more, pair it with other MyQ™ enabled accessories to monitor and control your garage door, gate and house lights from anywhere in the world via your Internet-enabled mobile phone or computer.

Our exclusive Security+ 2.0™ technology found in the LiftMaster® garage door opener remote controls, provides extra peace of mind for you and your family. This rolling code technology assures a new code with every use making it virtually impossible for anyone to steal your remote control signal.

Designed for how you live, LiftMaster® technology puts you in control.



Accessories Included:

Motion Detecting Control Panel (886LM)

- Activates the garage door opener lights as soon as you walk in, so there's no more fumbling in the dark to get in the car or grab something from the garage.
- Programming accessories is fast and easy with the new learn button.



3-Button Standard Remote Control (893LM)

- Controls up to three garage doors openers, commercial door operators, gates or MyQ™ enabled lighting accessories with this powerful remote control.
- Multi-frequency Security+ 2.0™ virtually eliminates interference.



At LiftMaster®, safety is a major part of our mission.

It's our commitment to you and, quite simply, the way we produce products every day. Our LiftMaster® products are designed to move the largest door in your home, safely, securely and by always putting safety first.

LiftMaster®

8360 DC BATTERY BACKUP CHAIN DRIVE GARAGE DOOR OPENER

Unmatched Communication, Safety & Security

LiftMaster® is making your home safer and more responsive to how you live.

- **Auto force and electronic limits** mean the garage door opener adapts to weather and changing environmental conditions, which means fewer call backs for you.
- **Security+ 2.0™ technology** is designed to communicate with the garage door opener in multiple frequencies. This enhanced radio virtually eliminates interference and provides you with the highest level of security.
- **The Protector System®** safety sensors project an invisible light beam across the garage door opening and automatically reverse the door if anything interrupts the beam while the door is going down. Garage door opener lights turn on automatically when the Protector System® infrared beam is broken.
- **Alert-2-Close** warning system provides UL325-compliant audible and visual warnings that the garage door is about to close when using the Timer-to-Close, or remote closing features. (Timer-to-Close is for sectional doors only, not one piece doors.)
- **Patented PosiLock®** system ensures the door remains securely locked when it is closed.



LiftMaster® MyQ™ Enabled Accessories: The Freedom to Enjoy Your Life

The 8360 is manufactured with built-in MyQ™ technology, which enables you to tap into even more features for maximum confidence, communication and compatibility.

LiftMaster® Internet Gateway (Model 828LM)
Uses MyQ™ technology to connect to and control your garage door opener or gate operator from anywhere via an Internet-enabled mobile phone or computer.



Remote Light Control (Model 825LM)
Operate any lamp with your garage door opener, remote control or from your Internet-enabled mobile phone or computer via the LiftMaster® Internet Gateway.



Garage and Gate Monitor (Model 829LM)
Uses MyQ™ technology to monitor and close your garage door or gate from any room in the house.



Remote Light Switch (Model 823LM)
Control lights remotely through the LiftMaster® Internet Gateway or garage door opener Security+ 2.0™ remote control.



Convenience on the go!

MAX Wireless Keyless Entry (Model 877MAX)
Features Security+ 2.0™ technology to open or close your garage door with a secure, private 4-digit code. Program temporary access codes for visitors or delivery and service personnel. Works with LiftMaster® garage door openers manufactured since January 1993. One button-to-close feature works with all LiftMaster® garage door openers manufactured since 2006.



LiftMaster®



The in-vehicle universal remote control. See your automobile dealer for availability.



I.C./F.C.C. Certified

*Uses HomeLink 5.0. May require an external adapter depending on the make, model and year of your vehicle. Visit www.homelink.com for additional information.

SPEC SHEET

STANDARD SPECIFICATIONS

DIMENSIONS:

Installed Length: 128"
Maximum Door Opening: 7' 3" *
Headroom Clearance Required: 2"
**Up to 10' with optional 8' or 10' rails*

CARTONS:

Number of Cartons: 3
Carton 1: Dimensions and Contents:
20" x 12" x 10"
886LM Motion-Detecting Control Panel
893LM 3 Button Remote Control
Garage Door Opener Head
The Protector System® Safety Reversing Sensors
Carton 2: Dimensions and Contents:
10' 4" x 5" x 5"
Assembled Solid-Steel T-Rail (Chain)
Carton 3: Dimensions and Contents:
5.31" x 4.63" x 5.13"
485LM Battery

SECURITY+2.0™ RADIO CONTROLS

Coding System: Smart Receiver Code Button and Indicator Light
893LM 3-Button Remote Control
Operating Range: 200' (approximately)
Operating Temperature: -40°F to 150°F
Frequency:
Remote Control: 310, 315 & 390 MHz Tri-Band
Receiver: Frequency Agile on 310, 315 & 390 MHz
Security+2.0™ Anti-Burglary Coding

MYQ™ RADIO

902-928 MHz
50 Channel FHSS (Frequency Hopping Spread Spectrum)
Provides two-way communication from garage door opener and MyQ™ enabled accessories
Enables remote closing of garage door with key MyQ™ accessories
Enables monitoring and control of garage door openers and lighting controls via internet-enabled computer or smartphone*
**Requires LiftMaster® Internet Gateway Accessory Model 828LM*

SECURITY+2.0™ ENCRYPTED CONTROLS

886LM Motion-Detecting Control Panel
Program Remote Controls
Maintenance Alert System

CONVENIENCE / SAFETY

The Protector System® Safety Reversing Sensors
Integrated Battery Back-Up System
Alert-2-Close Unattended Close Operation w/ Select Accessories **
Hands Free Work Lights On
Emergency/Quick Release
Automatic Trolley Reconnect
Ventilation /Pet Opening
Down Safety Reverse
Up Safety Stop
Door Open/Beam Obstructed/Lights On
Maintenance Alert System
PosiLock® secure lock system
Slow Start Soft Stop

***Unattended Operation functionality cannot be utilized when opener is installed on a one-piece door*

ELECTRICAL SPECIFICATIONS

POWER

Voltage: 120V AC, 60Hz
Wattage: 524 Total System (including lights)
Current Rating: 2.7A
UL Listings: Yes
Length of Line Cord: 4' (3-prong)

ENERGY EFFICIENCY

Approximately 1 Watt Power in Standby Mode***
Enhanced CFL (Compact Fluorescent) Compatible
†Standby Mode at down limit, work lights off

LOGIC TYPE

Solid State Microcontroller with Built-in Surge Suppressor

LIGHTING

Number of Bulbs: 2
Maximum Wattage: 100 x 2
Adjustable Time, Solid-State Delay
Enhanced CFL (Compact Fluorescent) Compatible, Max 27 Watts
In Battery Back-Up Mode: Disabled

MECHANICAL SPECIFICATIONS

MOTOR

800 Newtons
12V DC Motor
RPM: 53
Thermal Protection: Automatic
Lubrication: Permanent

DRIVE MECHANISM

Drive Means: Full Chain
Reduction Means: Gear 63:1
Door Linkage: Adjustable Door Arm

ADJUSTMENTS

Force: Electronic/Internal Auto Force
Limit: Internal Electronic

TRAVEL RATE

Approximately 8.0" per second in the up direction
Approximately 6.5" per second in the down direction

SHIPPING WEIGHTS

Head: 17.8 lbs.
Rail: 20 lbs.
Battery Backup: 3.9 lbs.

MATERIALS

Chassis and Chassis Cover: Steel
Rail: Solid-Steel T
Trolley: Steel

WARRANTY

Lifetime Motor Warranty
1 Years Parts Warranty
1 Year Battery Warranty (485LM)

HOMELINK® Compatible w/ QuickTrain™ Technology